

Typ: ViewPan PET

core material	WaveCore PET150-18/S
cover sheets	PET-G, polyester (thickness 1,5 mm transparent, 2 mm colourless satined)
colour	transparent, colourless satined or coloured coating by RAL or Pantone
weight	4,45 kg/m ² at 19mm thickness, 1,5mm cover sheet (transparent) 5,54 kg/m ² at 19mm thickness, 2mm cover sheet (colourless satined)
temperature application field	-20°C up to +70°C
combustibility	of low flammability (DIN 4102, Part 1-B1)
UV-resistance	good (transparent cover sheets can be equipped with UV-protection)
coefficient of thermal expansion	0,68mm/m at a temperature difference of 10°C
panel thickness	minimum 19mm, up to max.76mm any thickness (the tolerance in thickness is +-0,3mm)
edge closing	3mm PET-G transparent for both types (transparent and satined)

	ViewPan PET transparent	ViewPan PET colourless satined
maximum dimension after trim	3020 x 1200mm	
	3020 x 990mm	3020 x 990mm
	2470 x 1200mm	
	2020 x 1200mm	2020 x 1200mm
	2020 x 990mm	2020 x 990mm
	1620 x 1200mm	
	1620 x 990mm	
	1500 x 990mm	1500 x 990mm

Other dimensions and materials can be manufactured upon request.

Liability disclaimer: The above data are the best of our knowledge correct and are intended to give information about our products and their potential applications. No warranty is given or implied in respect of certain properties of the products or their suitability for a particular application. We guarantee impeccable product quality under our terms of sale.